

R12-100-/200-/110-/020-



R12-110-230V



1- and 2-pole, 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 1.9W.

Contacts: 1 NO, 2 NO, 1 NO a+ 1 NC, 2 NC (closed-circuit current relay, 230V only).

Contact gap 3 mm.

Contact/contact test voltage 2000 V and control connections/contact test voltage 4000 V.

25A devices XR12, page K2. Retrofittable auxiliary contact KM12, page J1.

* Non-standard control voltages: 42, 48, 60, 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 42, 48, 60, 110 and 220V DC.

Technical data page K3.

R12-100-12V	1 NO 16 A	EAN 4010312200421	
R12-100-230V	1 NO 16 A	EAN 4010312200445	
R12-100-8V, 24V, 12V DC, 24V DC	1 NO 16 A		
R12-100-*	1 NO 16 A		
R12-200-12V	2 NO 16 A	EAN 4010312200506	
R12-200-230V	2 NO 16 A	EAN 4010312200520	
R12-200-8V, 24V, 12V DC, 24V DC	2 NO 16 A		
R12-200-*	2 NO 16 A		
R12-110-12V	1NO + 1NC 16 A	EAN 4010312200469	
R12-110-230V	1NO + 1NC 16 A	EAN 4010312200483	
R12-110-8V, 24V, 12V DC, 24V DC	1NO + 1NC 16 A		
R12-110-*	1NO + 1NC 16 A		
R12-020-230V	2 NC 16 A	EAN 4010312201572	